



版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	600V/30A	1000V/41A
压线范围 (Wire Range)	14~10AWG	0.5~6.0mm <sup>2</sup>
工频耐压 (Frequency Voltage)	AC 3000V	
冲击耐压 (Rated Surge Voltage)	6000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500M $\Omega$ above	
接触电阻 (Contact Resistance)	$\leq 8m\Omega$	
剥线长度 (Stripping Length)	6~7	
工作温度 (Temperature)	-40 $^{\circ}$ C~+105 $^{\circ}$ C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-2)	
接线柱 (Contact Block)	铜合金, 镀镍 (Copper alloy, Ni plated)	
螺丝 (Screws)	钢, 镀锌 (Steel, Zn plated)	

产品命名编码:  
(Product Number Code):  
**GSS300HW-12.0-XXP-1Y-00A (H)**

产品型号 (Series No.)      客户需求 (Customer Request)  
极数 (No. of poles)      塑体颜色 (Housing Color)

- |                        |                       |
|------------------------|-----------------------|
| 1: 单倍间距 (Single Pitch) | 7: 透明色 (Transparent)  |
| 2: 双倍间距 (Double Pitch) | 8: 白色 (White)         |
| 3: 黑色 (Black)          | 9: 黄色 (Yellow)        |
| 4: 灰色 (Grey)           | Y: 多种颜色 (Mixed Color) |
| 5: 橙色 (Orange)         |                       |
| 6: 红色 (Red)            |                       |

P=12.00mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~12P

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P
L	19.50	31.50	43.50	55.50	67.50	79.50	91.50	103.50	115.50	127.50	139.50
B	12.00	24.00	36.00	48.00	60.00	72.00	84.00	96.00	108.00	120.00	132.00

**GOOSVN 宁波高胜电子有限公司**  
NINGBO GOOSVN ELECTRONIC CO.,LTD

公差范围 (Tolerance Range)

150~	$\pm 1.50$
60~150	$\pm 1.00$
30~60	$\pm 0.60$
6~30	$\pm 0.40$
0~6	$\pm 0.25$
角度 (Angle)	X $\pm 2^{\circ}$
	XX $\pm 1^{\circ}$

型号 (Type): GSS300HW-12.0-XXP-1Y-00A (H)

核准 (Approval):      图号 (Drawing NO.):

审核 (Audit):      单位 (Units): mm      页码 (Page): 1/1

设计 (Design):      比例 (Scale): FULL      版次 (Version): T0