


版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	600V/50A	1000V/57A
压线范围 (Wire Range)	12~8AWG	0.5~10.0mm <sup>2</sup>
工频耐压 (Frequency Voltage)	AC 3000V	
冲击耐压 (Rated Surge Voltage)	6000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	6~7	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-2)	
接线柱 (Contact Block)	铜合金, 镀镍 (Copper alloy, Ni plated)	
螺丝 (Screws)	钢, 镀锌 (Steel, Zn plated)	

产品命名编码:

(Product Number Code):

GSS400-13.5-XXP-1Y-00A (H)



1: 单倍间距 (Single Pitch)	1: 绿色 (Green)	7: 透明色 (Transparent)
2: 双倍间距 (Double Pitch)	2: 蓝色 (Blue)	8: 白色 (White)
	3: 黑色 (Black)	9: 黄色 (Yellow)
	4: 灰色 (Grey)	Y: 多种颜色 (Mixed Color)
	5: 橙色 (Orange)	
	6: 红色 (Red)	

P=13.50mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~12P

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P
L	22.90	36.40	49.90	63.40	76.90	90.40	103.90	117.40	130.90	144.40	157.90
B	13.50	27.00	40.50	54.00	67.50	81.00	94.50	108.00	121.50	135.00	148.50

<b>宁波高胜电子有限公司</b> NINGBO GOOSVN ELECTRONIC CO.,LTD	公差范围 (Tolerance Range)	
	150~	±1.50
型号 (Type): GSS400-13.5-XXP-1Y-00A (H)	60~150	±1.00
	30~60	±0.60
核准 (Approval):	6~30	±0.40
	0~6	±0.25
审核 (Audit):	角度 (Angle)	X ±2°
	XX	±1°
设计 (Design):	比例 (Scale): FULL	版次 (Version): T0