



版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/15A	630V/32A
压线范围 (Wire Range)	22~14AWG	4.0mm <sup>2</sup>
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	6000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	6~7mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺丝 (Screws)	钢, 镀镍 (Steel, Nickel plating)	

产品命名编码:  
(Product Number Code):

**GSA24R-10.0-XXP-1Y-00A (H)**

产品型号 (Series No.)      客户需求 (Customer Request)  
极数 (No. of poles)      塑体颜色 (Housing Color)

1: 单倍间距 (Single Pitch)	7: 透明色 (Transparent)
2: 双倍间距 (Double Pitch)	8: 白色 (White)
	9: 黄色 (Yellow)
	Y: 多种颜色 (Mixed Color)

P=10.0mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 2\*(02P~24P)

N	2*02P	2*03P	2*04P	2*05P	2*06P	2*07P	2*08P	2*09P	2*10P	2*11P	2*12P	2*13P	2*14P
L	37.30	47.30	57.30	67.30	77.30	87.30	97.30	107.30	117.30	127.30	137.30	147.30	157.30
S	28.50	38.50	48.50	58.50	68.50	78.50	88.50	98.50	108.50	118.50	128.50	138.50	148.50
D	21.60	31.60	41.60	51.60	61.60	71.60	81.60	91.60	101.60	111.60	121.60	131.60	141.60
B	10.00	20.00	30.00	40.00	50.00	60.00	70.00	80.00	90.00	100.00	110.00	120.00	130.00
N	2*15P	2*16P	2*17P	2*18P	2*19P	2*20P	2*21P	2*22P	2*23P	2*24P			
L	167.30	177.30	187.30	197.30	207.30	217.30	227.30	237.30	247.30	257.30			
S	158.50	168.50	178.50	188.50	198.50	208.50	218.50	228.50	238.50	248.50			
D	151.60	161.60	171.60	181.60	191.60	201.60	211.60	221.60	231.60	241.60			
B	140.00	150.00	160.00	170.00	180.00	190.00	200.00	210.00	220.00	230.00			

**宁波高胜电子有限公司**  
NINGBO GOOSVN ELECTRONIC CO.,LTD

公差范围 (Tolerance Range)	
150~	±1.50
60~150	±1.00
30~60	±0.60
6~30	±0.40
0~6	±0.25
角度 (Angle)	X ±2°
	XX ±1°

型号 (Type): GSA24R-10.0-XXP-1Y-00A (H)

核准 (Approval):	图号 (Drawing NO.):
审核 (Audit):	单位 (Units): mm      页码 (Page): 1/1
设计 (Design):	比例 (Scale): FULL      版次 (Version): T0