



版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/10A	450V/15A
压线范围 (Wire Range)	22~16AWG	1.5mm ²
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	11mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺钉 (Screwing)	不锈钢 (Stainless)	

产品命名编码:
(Product Number Code):
GSL004R-7.62-XXP-1Y-00A (H)

产品型号 (Series No.) | 客户需求 (Customer Request)
极数 (No. of poles) | 塑体颜色 (Housing Color)

1: 单倍间距 (Single Pitch)	7: 透明色 (Transparent)
2: 双倍间距 (Double Pitch)	8: 白色 (White)
	9: 黄色 (Yellow)
	Y: 多种颜色 (Mixed Color)
	6: 红色 (Red)

P=7.62mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 01P~XXP

N	01P	02P	03P	04P	05P	06P	07P	N	08P	09P	10P	11P	12P	13P	14P
L	7.62	15.24	22.86	30.48	38.10	45.72	53.34	L	60.96	68.58	76.20	83.82	91.44	99.06	106.68
B	/	7.62	15.24	22.86	30.48	38.10	45.72	B	53.34	60.96	68.58	76.20	83.82	91.44	99.06
N	15P	16P	17P	18P	19P	20P	21P	N	22P	23P	24P	25P	26P	27P	...
L	114.30	121.92	129.54	137.16	144.78	152.40	160.02	L	167.64	175.26	182.88	190.50	198.12	205.74	
B	106.68	114.30	121.92	129.54	137.16	144.78	152.40	B	160.02	167.64	175.26	182.88	190.50	198.12	

GOOSVN 宁波高胜电子有限公司
NINGBO GOOSVN ELECTRONIC CO.,LTD

公差范围 (Tolerance Range):
150~ ±1.50
60~150 ±1.00
30~60 ±0.60
6~30 ±0.40
0~6 ±0.25

型号 (Type): **GSL004R-7.62-XXP-1Y-00A (H)**

核准 (Approval): | 图号 (Drawing NO.):
审核 (Audit): | 单位 (Units): mm | 页码 (Page): 1/1
设计 (Design): | 比例 (Scale): FULL | 版次 (Version): T0