


版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/20A	450V/24A
压线范围 (Wire Range)	22~12AWG	2.5mm ²
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	6~7mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺丝 (Screws)	钢, 镀镍 (Steel, Nickel plating)	



产品命名编码:

(Product Number Code):

GSA30C-8.25-XXP-1Y-00A (H)

产品型号 (Series No.)

客户需求
(Customer Request)

极数 (No. of poles)

塑体颜色 (Housing Color)

- 1: 单倍间距 (Single Pitch)
- 2: 双倍间距 (Double Pitch)

- 7: 透明色 (Transparent)
- 8: 白色 (White)
- 9: 黄色 (Yellow)
- Y: 多种颜色 (Mixed Color)
- 3: 黑色 (Black)
- 4: 灰色 (Grey)
- 5: 橙色 (Orange)
- 6: 红色 (Red)
- 2: 蓝色 (Blue)
- 1: 绿色 (Green)

P=8.25mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~26P

N	02P	03P	04P	05P	06P	07P	N	08P	09P	10P	11P	12P	13P	14P
L	18.45	26.70	34.95	43.20	51.45	59.70	L	67.95	76.20	84.45	92.70	100.95	109.20	117.45
B	8.25	16.50	24.75	30.00	41.25	49.50	B	57.75	66.00	74.25	82.50	90.75	99.00	107.25
N	15P	16P	17P	18P	19P	20P	N	21P	22P	23P	24P	25P	26P	
L	125.70	133.95	142.20	150.45	158.70	166.95	L	175.20	183.45	191.70	199.95	208.20	216.45	
B	115.50	123.75	132.00	140.25	148.50	156.75	B	165.00	173.25	181.50	189.75	198.00	206.25	

宁波高胜电子有限公司
 NINGBO GOOSVN ELECTRONIC CO.,LTD

公差范围 (Tolerance Range)
 150~ ±1.50
 60~150 ±1.00
 30~60 ±0.60
 6~30 ±0.40
 0~6 ±0.25

型号 (Type): GSA30C-8.25-XXP-1Y-00A (H)

核准 (Approval): 图号 (Drawing NO.):
 审核 (Audit): 单位 (Units): mm 页码 (Page): 1/1
 设计 (Design): 比例 (Scale): FULL

版次 (Version): T0