



版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/16A	400V/18A
压线范围 (Wire Range)	28~12AWG	0.2~2.5mm <sup>2</sup>
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	6000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤20mΩ	
剥线长度 (Stripping Length)	7mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀镍 (Copper alloy, Ni plated)	
螺丝 (Screws)	钢, 镀锌 (Steel, Zn plated)	
方盒 (Cage)	铜合金, 镀镍 (Copper alloy, Ni plated)	

产品命名编码:  
(Product Number Code):  
**GSP001A-7.62-XXP-1Y-00A (H)**

产品型号 (Series No.)      客户需求 (Customer Request)  
极数 (No. of poles)      塑料颜色 (Housing Color)

- |                        |                       |
|------------------------|-----------------------|
| 1: 单倍间距 (Single Pitch) | 7: 透明色 (Transparent)  |
| 2: 双倍间距 (Double Pitch) | 8: 白色 (White)         |
|                        | 9: 黄色 (Yellow)        |
|                        | Y: 多种颜色 (Mixed Color) |
|                        | 6: 红色 (Red)           |

P=7.62mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~24P

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	13.62	21.24	28.86	36.48	44.10	51.72	59.34	66.96	74.58	82.20	89.82	97.44
B	7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	91.44
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	
L	105.06	112.68	120.30	127.92	135.54	143.16	150.78	158.40	166.02	173.64	181.26	
B	99.06	106.68	114.30	121.92	129.54	137.16	144.78	152.40	160.02	167.64	175.26	

**GOOSVN** 宁波高胜电子有限公司  
NINGBO GOOSVN ELECTRONIC CO.,LTD

型号 (Type): GSP001A-7.62-XXP-1Y-00A (H)

核准 (Approval):      图号 (Drawing NO.):

审核 (Audit):      单位 (Units): mm      页码 (Page): 1/1

设计 (Design):      比例 (Scale): FULL      版次 (Version): T0

公差范围 (Tolerance Range):  
150~ ±1.50  
60~150 ±1.00  
30~60 ±0.60  
6~30 ±0.40  
0~6 ±0.25

角度 (Angle): X ±2°  
XX ±1°